



US009638381B2

(12) **United States Patent**
Cavaliere et al.

(10) **Patent No.:** **US 9,638,381 B2**

(45) **Date of Patent:** **May 2, 2017**

(54) **IN-GROUND LIGHT FIXTURE SYSTEM
WITH IMPROVED INSTALLATION
CLOSURE MECHANISM AND DRAINAGE**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **Lumenpulse Lighting Inc.**, Montreal,
Quebec (CA)

4,035,632 A 7/1977 Rayman
4,907,361 A * 3/1990 Villard G09F 19/228
362/153

(72) Inventors: **David Cavaliere**, Lachine (CA); **Yvan
Hamel**, Laval (CA); **Jean-Philippe
Pellan**, Sainte-Melanie (CA)

(Continued)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Lumenpulse Lighting Inc.** (CA)

CA 2451340 5/2004

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 198 days.

OTHER PUBLICATIONS

Search Report and Written Opinion mailed Dec. 17, 2015 in
corresponding PCT Application No. PCT/IB2015/001631 filed May
27, 2015.

Primary Examiner — Peggy Neils

(74) *Attorney, Agent, or Firm* — Burns & Levinson LLP;
Joseph M. Maraia

(65) **Prior Publication Data**

US 2015/0345722 A1 Dec. 3, 2015

Related U.S. Application Data

(60) Provisional application No. 62/003,463, filed on May
27, 2014.

(51) **Int. Cl.**
F21S 4/00 (2016.01)
E04F 19/02 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **F21S 8/022** (2013.01); **F21V 5/04**
(2013.01); **F21V 17/107** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC F21S 8/022; F21S 4/20; F21S 4/28; F21V
19/001; F21V 5/04; F21V 33/006; F21V
17/07; F21W 2131/10; B64F 1/205
See application file for complete search history.

(57) **ABSTRACT**

A lighting system includes a linear light fixture and a linear
blockout structure. The linear blockout structure includes a
chamber in which the linear light fixture is mountable and
side walls on opposite sides of the chamber engageable by
flange portions of the linear light fixture when the linear light
fixture and linear blockout structure are assembled together.
A hinge structure includes first and second hinge compo-
nents engaging each other such that when the linear blockout
structure and linear lighting fixture are being assembled,
they are rotatable with respect to each other at the hinge
structure. First and second fastening components engage
each other to hold the linear blockout structure and linear
lighting fixture assembled together with the linear light
fixture being disposed within the chamber of the linear
blockout structure.

11 Claims, 23 Drawing Sheets

